



manufacturer and stockist of wire and strip

STAINLESS STEEL WIRE FOR SPRINGS

Head Office

Webster & Horsfall Limited
Hay Mills, Birmingham B25 8DW
West Midlands, United Kingdom

Tel: +44 (0)121 772 2555 **Fax:** +44 (0)121 766 5816

E-mail: sales@websterandhorsfall.co.uk

www.websterandhorsfall.co.uk

Sales Office

Tel: +44 (0)121 772 9797 **Fax:** +44 (0)121 766 5816

STAINLESS STEEL WIRES (AUSTENITIC)

Applications Corrosion resistant mechanical springs, extension, compression and tension.

Standards	EN 10270-3 BS 2056 NF A35-587 DIN 17224 ASTM A313+A580	European Great Britain France German USA	Type 302, 316 or 321.
Diameter range	0.1mm – 9.5mm (Type 302) 0.1mm – 4.0mm (Type 316 + 321)		
Tensile range	695 N/mm ² – 2600 N/mm ²		
Finish	Phosphate coated (plain) Wet drawn Linished Degreased	– Dry drawn wire with soap lubricants – Oil drawn polished finish – Mechanically ground polish finish – Chemically degreased/desoaped (in coil only)	
Shaped	The above can also be supplied in shaped wire. (Please see separate sheet)		
Packaging	Catchweight coils Reels/spools (plastic) Metal reels (up to 300 kgs) Formers Cut lengths Specific coil weights/sizes (see Packaging separate sheet)		

