



WIRE MANUFACTURERS EST. 1720

**Head Office**

Webster & Horsfall Limited  
 Hay Mills, Birmingham B25 8DW  
 West Midlands, United Kingdom  
**Tel:** +44 (0)121 772 2555 **Fax:** +44 (0)121 766 5816  
**E-mail:** sales@websterandhorsfall.co.uk  
**www.websterandhorsfall.com**

**Sales Office**

**Tel:** +44 (0)121 772 9797 **Fax:** +44 (0)121 766 5816



**DRAWN SQUARE WIRE**

Hard Drawn	Carbon Spring Wire 0.71mm - 8.0mm Stainless spring wire 0.8mm - 5.53mm
------------	---

Annealed	Carbon and low alloy spring wire 0.8mm – 9.5mm
----------	---

**ROLLED SECTION WIRE**

Hard drawn	Carbon and stainless steel spring wire (stainless by special arrangement - maximum width 4mm)	
	width maximum 9.5mm	thickness range 0.5mm – 3.26mm
	width minimum 1.0mm	thickness range 0.4mm – 0.9mm

Oil Tempered	Carbon and low alloy spring steel wire (round edge only)	
	width maximum 12.5mm	thickness range 1.63mm – 6.35mm
	width minimum 1.27mm	thickness range 0.5mm – 1.0mm

Annealed	Carbon and low alloy	
	width maximum 12.5mm	thickness range 0.5mm – 6.35mm
	width minimum 1.0mm	thickness range 0.4mm – 0.89mm

Special shapes and sections AI and HM rope sections, special spring wire sections. ie diamonds, hexagons and trapezoidals, can be manufactured by special arrangement, please advise us of your requirements.

