



WIRE MANUFACTURERS EST. 1720

Head Office

Webster & Horsfall Limited
Hay Mills, Birmingham B25 8DW
West Midlands, United Kingdom

Tel: +44 (0)121 772 2555 **Fax:** +44 (0)121 766 5816

E-mail: sales@websterandhorsfall.co.uk

www.websterandhorsfall.com

Sales Office

Tel: +44 (0)121 772 9797 **Fax:** +44 (0)121 766 5816

STAINLESS STEEL BELTING AND WEAVING WIRE

Applications	ASTM, JIS, EN and other international standards and customised specifications to meet customer requirements		
Standards	EN 10270-3 BS 2056 NF A35-587 DIN 17224 ASTM A313+A580	European Great Britain France German USA	Grade: 302, 304, 304L, 305, 310S, 314, 316, 316L, 321 etc
Production Range	0.60 ~ 7.50 mm		
Tensile range	695 N/mm ² – 2600 N/mm ²		
Surface	Provide various kinds of surface such as BR, Extra BR etc. (BR: Bright Surface with no Lubricant)		
Shaped	The above can also be supplied in shaped wire. (Please see separate sheet)		
Packaging	Provide various packing type to meet required unit weight. (Spool, Carrier, Coil) (see Packaging separate sheet)		

- - Minimal Surface Roughness
- - Clean Finish
- - Food Contract Safe
- - Different Levels of Brightness
- - Excellent Cast Helix Control
- - Customer Specific Tensile and Sizes

