



Webster & Horsfall

WIRE MANUFACTURERS EST. 1720

Head Office

Webster & Horsfall Limited
 Hay Mills, Birmingham B25 8DW
 West Midlands, United Kingdom
Tel: +44 (0)121 772 2555 **Fax:** +44 (0)121 766 5816
E-mail: sales@websterandhorsfall.co.uk
www.websterandhorsfall.com

Sales Office

Tel: +44 (0)121 772 9797 **Fax:** +44 (0)121 766 5816

STAINLESS STEEL WIRES (AUSTENITIC)

Applications Corrosion resistant mechanical springs, extension, compression and tension.

Standards	EN 10270-3	European	Grade: 302, 316, 316, 321
	BS 2056	Great Britain	
	NF A35-587	France	
	DIN 17224	German	
	ASTM A313+A580	USA	

Production Range 0.1mm - 9.5mm (Type 302)
 0.1mm - 4.0mm (Type 316 + 321)

Tensile range 695 N/mm² – 2600 N/mm²

Surface	Phosphate coated (plain)	– Dry drawn wire with soap lubricants
	Wet drawn	– Oil drawn polished finish
	Linished	– Mechanically ground polish finish
	Degreased	– Chemically degreased/desoaped (in coil only)

Shaped The above can also be supplied in shaped wire. (Please see separate sheet)

Packaging Catchweight coils, Reels/spools (plastic), Metal reels (up to 300 kgs), Formers, Cut lengths, Specific coil weights/sizes etc. (Please see separate sheet)

- -Minimal Surface Roughness
- - Clean Finish
- - Food Contract Safe
- - Different Levels of Brightness
- - Excellent Cast Helix Control
- - Customer Specific Tensile and Sizes

